

SYNTHETIC BLEND

RACING

ROTARY FUEL LUBE (PREMIX)

This formulation has been specifically engineered to provide additional protection for rotary engines throughout their unique combustion conditions. The technology base for this formulation utilizes IDEMITSU's experience with the first 24 hour Le Mans winner using a rotary engine for which IDEMITSU developed the winning oil.

- Reduces Deposits and Subsequent Exhaust Port Clogging
- Special Detergents/Dispersant Additives Keep Your Fuel Injectors Clean to Reduce Maintenance
- Provides Additional Wear Protection For Apex Seals, Side Seals, etc.
- Reduces Friction

Application:

Inherently with many rotary engines, the entirety of the rotor and housing are not being sufficiently lubricated, resulting in premature wear or damage. In order to increase lubrication within the rotary, Idemitsu developed Idemitsu Rotary Premix. At ½ oz per gallon of fuel, it is a cost effective way lubricate more of your engine and prevent premature catastrophic damage.

- ½ oz per gallon of fuel

Characteristics:

Exceeds JASO FC Classifications

Viscosity @ 40°C 52.92 cSt

 @ 100°C 8.52 cSt

Viscosity Index: 136

Pour Point: -39°C

Flash Point: 126°C

Packaging:

Quart (.946 L)



IDEMITSU Racing USA

Manufactured & Distributed by Idemitsu Lubricants America Corporation

Headquarters:

701 Port Rd.,
Jeffersonville, IN 47130
www.idemitsu-usa.com

LA Sales Office:

21241 S. Western Ave. Ste. 130
Torrance, CA 90501
(310) 563-1930
lasales@ilacorp.com